



Qinyuan Bearing Manufacturing Co., Ltd.

1.688 Inch | 42.875 Millimeter x 2.875 Inch |
 73.02 Millimeter x 2.125 Inch | 53.98 Millimeter
 SKF SYR 1.11/16 Pillow Block Bearings



Bearing No. SYR 1.11/16

SYR 1.11/16 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.68
EAN	7316576674518
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Concentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22209
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row Heavy Duty Open End With Set Screw
Long Description	2 Bolt Pillow Block; 1-11/16" Bore; 2-1/8" Base to Center Height; Concentric Collar Mount; Spherical Roller Bearing;



Qinyuan Bearing Manufacturing Co., Ltd.

	5-3/16" Minimum Bolt Spacing; 5-13/16" Bolt Spacing Maximum; Re
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SYR 1.11/16
Weight / LBS	8.1
B	2.125 Inch 53.98 Millimeter
D	2.875 Inch 73.02 Millimeter
Nominal Bolt Center to Center	5.5 Inch 140 Millimeter
d	1.688 Inch 42.875 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Maximum	5.813 Inch 147.65Millimeter
Bolt Spacing Minimum	5.188 Inch 131.775Millimeter
bore diameter:	1.6875 in
bolt center-to-center length:	5-1/2 in
overall length:	7.3750 in
base width:	2-1/16 in
overall height:	4.2500 in
expansion type:	Expansion Bearing (Floating)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller



Qinyuan Bearing Manufacturing Co., Ltd.

seal type:	Tri-Guard
bore type:	Round
radial dynamic load capacity:	20000 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	19600 lbf
base to bore centerline:	2.1250 in
maximum rpm:	2300 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Concentric Collar
replacement bearing:	22209